رم م

芯	臺	8						
-		PRESS	MAIL	Mailing	Label No.	TB 057	257 05	7 US
ᇹ		20						



PTO/SB/05 (6-95) Approved for use through 11/30/98 OMB 0651-0032 Patent and Trademark Office: US Department of Commerce

pe a pius sign (+) nere → +		
De a plus sign (US Department of Commerce	Attorney Docket Number	
Rev. 6/95	Patent and Trademark Office	•	ARC 2600 R1
NEW UTILITY PATENT			
		First Named Inventor	THEEUWES, Felix, et al.
APPLICATION TRANSMITTAL		Total Pages in this	
711 1 21071	TOTAL TREATMENT TALE	Submission	

APPLICATION ELEMENTS								
Note: Checklist items mentioned under Application Elements section construct a new ubtity patent application. Please rater to MPEP Sections 506,801, (37 CFR 177, 153, 35 USC 511, 112, 113) for detailed explanation regarding completeness of an original patent application.			ACCOMPANYING APPLICATION PARTS					
1 🛭	Fee Transmittal Fe	orm (prescribed filing fee(s))		6 🔲 /	Assignment Pa	pers		
2. 🛛	Specification			7 🔲 (Certified Copy	of Priority I	Document(s) (if foreign priority is claimed)	
	Title of the Inventi	on		8 🔲	Computer Prog	ram in Mic	rofiche	
	Cross References	to Related Applications (if applicable)		9. 🔲 1	English Transla	tion Docum	ment (if applicable)	
	Statement Regard	ding Federally-sponsored Research/Develop	oment (#		Information Dis Statement/PTC		Copies of IDS Citations	
	Reference to Micr	rofiche Appendix (if applicable)		11 🔲 1	Petition Checkl	ist and Ac	companying Petition	
	Background of the	e Invention		12 🔲 1	Preliminary Am	endment		
	Brief Summary of	the Invention		13 🔲 I	Proprietary Info	rmation		
	Brief Description	of the Drawings (If drawings filed)		14 Return Receipt Postcard				
	Detailed Description			15. Small Entity Statement				
Claim or Claims			16. Additional Enclosures (please identify below)					
	Abstract of the Di	sclosure						
з. 🖂	Drawing(s) (when	necessary as prescribed by 35 USC 113)						
4. 🖂	Executed Declara	ation						
5.	Genetic Sequeno	e Submission (if applicable, all must be incl	uded)					
	Paper Copy							
	Computer Readal	ble Copy						
	Statement Verifyi	ng Identical Paper and Computer Readable	Сору					
ADDRESS OF APPLICANT, ATTORNEY, OR AGENT				URE OF API	LICANT	, ATTORNEY, OR AGENT		
ALZA Corporation			Firm or Individua	al name	D Byro	n Miller		
950 Page Mill Road P.O. Box 10950					(// W/M		
Palo Alto, CA 94303-0802			Signatur	e	1	18/1/hlh		
			Date		Decem	ber 10 , 1997		
FOR OFFICE				AL USE O	NLY		Index and and Claims	
	of Receipt	Application Type:	Class:				Independent Claims: Total Claims:	
Date	or receipt	Filing Date:		Filing Lice	nse?:		Drawing Sheets:	
		Small Entity:		Address?:			Special Handling?:	
	TO: DOW DATENT	ADDLICATION Assistant Commissioner fo	- Dotonio V	Machington	00 00004			

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 C.F.R. § 1.10. Express Mail meilling label no. TB 057 257 057 US, addressed to Box PATENT APPLICATION, Assistant Commissioner for Patents, Washington, D.C. 2023 ton December 20, 1997 (date)

Volaw

PTO/SB/17 (6-95)
Approved for use through 11/30/98 OMB 0651-0032
Patent and Trademark Office: US Department of Commerce

0002/PTO			Complete if Known					
Rev. 10/95			Application Number					
		Filing Date						
FEE TRANSMITTAL			First Named Inventor	THEEUWES, Felix, et al.				
			Group Art Unit					
Total Amount of Payment		(\$) 900.00	Examiner Name					
			Attorney Docket Number	ARC 2600 R1				

METHOD OF PAYMENT (check one)	FEE CALCULATION (continued)						
The Commissioner is hereby authorized to charge indicated fees	3	3 ADDITIONAL FEES					
and credit any over payments to	Lare	e En	tity Small	Entity	,		
Deposit	Fee	Fee (e (\$)	Fee Code	Fee (\$)	Fee Description	Fee Paid	
Account Number: 01-1173	105			65	Surcharge-late filing fee		
Deposit					or oath		
Account Name: ALZA Corporation	127	51	227	25	Surcharge-late provisions filing fee or cover sheet.	al	
	139			130 2,520	Non-English specification For filing a request for	١	
Charge Any Additional Charge the Issue Fee Set	1			920*	reexamination Requesting publication of	6 P.ID	
37 CFR 1.16 and 1.17 Mailing of the Notice of	112		-		prior to Examiner action		
Allowance, 37 CFR 1 311(b)	113	1,84	0* 113	1,840*	Requesting publication of after Examiner action	fSIR	
	115	110	215	55	Extension for response w first month	vithin	
2 Payment Enclosed:	116	40	216	200	Extension for response was second month	vithin	
Check Money Order Other	117	95	217	475	Extension for response w	vithin	
FEE CALCULATION (fees effective 10/1/97)	118	1,51	218	755	third month Extension for response w	vithin	
1 FILING FEE	١				fourth month		
Large Entity Small Entity	119			155 155	Notice of Appeal Filing a brief in support of	f	
• •					an appeal		
Fee Fee Fee Fee Fee Paid Code (\$) Code (\$) Description	121			135 1,510	Request for oral hearing Petition to institute a pub	lie	
Code (\$) Code (\$) Description	130	1,51	0 136	1,510	use proceeding	IIC	
101 790 201 395 Utility filing 790 00 106 330 206 165 Design filing fee	140	11	0 240	55	Petition to revive unavoid abandoned application	lably	
107 540 207 270 Plant filing fee 108 790 208 395 Reissue filing fee	141	1,32	0 241	660	Petition to revive unintentionally abandone		
114 150 214 75 Provisional filing fee					application		
01070741 (4) (2) 700 00	142			660 225	Utility issue fee (or reissu	ie)	
SUBTOTAL (1) (\$) 790.00	143			335	Design issue fee Plant issue fee		
	122			130	Petitions to the Commiss	sioner	
2 CLAIMS Fee from Extra below Fee Paid	123	5 5	0 123	50	Petitions related to provis applications	sional	
Total Claims 25-20 = 5 x 22 = 110.00	126	24	0 126	240	Submission of Informatio Disclosure Statement	in	
Independent	581	4	0 581	40	Recording each patent assignment per property		
Claims 3-3 = 0 x = 0.00					(x no. properties)		
Multiple Dependent Claims x = 0.00	146	3 79	0 246	395	Filing a submission after final rejection		
Large Entity Small Entity	149	79	0 249	395	(37 CFR 1.129(a)) For each additional inver	ntion	
Fee Fee Fee Fee Code (\$) Code (\$) Fee Description					to be examined (37 CFR 1.129(b))		
103 22 203 11 Claims in excess of 20							
102 82 202 41 Independent claims in excess of 3	Oth	er fee (sp	ecify)				
104 270 204 135 Multiple dependent claim							
109 82 209 41 Reissue independent claims over original patent	Oth	er fee (sp	ecify)				
110 22 210 11 Reissue claims in excess of 20 and over original patent	Jul	roc (3p			SUBTOTAL (3)		
SUBTOTAL (2) (\$) 110.00	+R	educed by	Basic Filing I	Fee Paid			
SUBMITTED BY					Complete (if applicable)		
Typed or Printed Name D, Byron Miller				T	Reg. Number: 30	0,661	
Signature S Su Mills		Date:	December j 1997	0	Deposit Account	1-1173	

SEND TO: Box Patent Application, Assistant Commissioner for Patents, Washington, DC 20231.

Type a plus sign (+) here →

OO10/PTO US Depart	ment of Commerc		Attorney Docket Number	LABOS	600 R1				
Rev. 12/95 Patent and Trademark Office			irst Named Inventor	THEEUWES, Felix, et al.					
	-	F	COMPLETE IF KNOWN:						
DECLARA	TION	7	Application Number						
		-	iling Date	<u> </u>					
Declaration	Declaration	-	Group Art Unit	+					
Submitted with OR	Submitted after		Examiner Name	1					
Initial Filing	Capitalian Man Cit Capitalian City								
Timed 1 mig	THE COLOR TO STATE OF								
As a below named inventor, I h	ereby declare that								
My residence, post office address, and citizenship are as stated below next to my name.									
I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:									
DEVICE AND METHOD FOR	ENHANCING TRA	NSDER	MAL AGENT FLUX						
			(Title of the Invention)				ļ		
the specification of which									
is attached hereto									
OR									
was filed on (MM/DD/YY)	YY as United	States	Application Number or PCT	Γ Internat	tional				
Application Number and	i was amended on	(MM/DI	D/YYYY) (if applicable	e)					
I hereby state that I have revie any amendment specifically re		d the c	ontents of the above identific	ed specil	fication, including th	ne claims, as an	ended by		
I acknowledge the duty to disc	lose information w	ich is r	naterial to patentability as de	efined in	Title 37 Code of Fe	deral Regulatio	ns, § 1.56.		
I hereby claim foreign priority to inventor's certificate, or § 365(America, listed below and have	 a) of any PCT interest e also identified be 	nationa ow, by	I application which designate checking the box, any foreign	ed at lea in applic	st one country othe ation for patent or in	r than the Unite	d States of		
any PCT international applicat	ion having a filing o	ate bef		which p	riority is claimed.	C 44			
Prior Foreign Application Number(s)	Country		Foreign Filing Date (MM/DD/YYYY)	Priori	ty Not Claimed	Copy Att Yes	No		
Additional foreign application numbers are listed on a supplemental priority sheet attached hereto:									
I hereby claim the benefit under Title 35, United States Code § 119(e) of any United States provisional application(s) listed below. Application Number(s) Filling Date (MM/DD/YYYY)									
Application Number(s) 60/033,440		2/20/96					ication		
00,000,440	'					re listed on a su			
1						et attached her			

SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

DECLARATION	Page 2

I hereby claim the benefit under Title 35, United States Code § 120 of any United States application(s), or § 365(c) of any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code § 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations § 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

US Parent Application PCT Parent Number Number					t Filing Date		Parent Patent Number (if applicable)		
Number	N	niiber		(MM/DD/YYYY)			(п аррисаоте)		
	1								
						1			
	L						- Marrier		
Additional US or PCT interna	ational applicatio	n numbers	are listed	on a supplem	ental priority s	sheet attached	d hereto.		
As a named inventor, I hereby ap	point the following	ng attorney	(s) and/or	agent(s) to pr	osecute this a	nnlication and	to transact all business in		
the Patent and Trademark Office			(a) androi	ageni(a) to pi	oscoule this u	ppilodilon dire	to transact an basiness in		
					_				
Firm Name: ALZA Corporation					Payor Numbe	er: 01-1173	•		
					(if applica)		
Name		stration N	umber		Name		Registration Number		
Steven F. Stone	20,246			D. Byron Mil			30,661		
Paul L. Sabatine Michael J. Rafa	22,539 38.740			John A. Dhu Christopher			26,265 36.334		
Michael J. Rala	30,741	,		Pauline Ann			29.783		
							,		
Additional attorney(s) and/or	agent(s) named	on a supp	lemental	sheet attached	d hereto.				
Please direct all corresponde	ence to:								
Name:									
D. Byron Miller									
Address: ALZA Corporation									
Address:									
950 Page Mill Roa	ad			State:	Zip				
Palo Alto				CA		94303-080	12		
Country:			Tele	phone:	`	Fax:	JE		
U.S.A.				(650)	496-8150		650) 496-8048		
I hereby declare that all statement									
believed to be true; and further th									
punishable by fine or imprisonme may jeopardize the validity of the					nited States Ci	ode and that	such willful false statements		
Name of Sole or First Inventor:		ny patent i	saueu me	ieon.					
Name of Both of The Internation		petition h	as been fi	led for this uns	signed inventor	r.			
Felix Theeuwes					•				
Given Middle Name: Felix Initial:				Family Suffix:			Suffix:		
Name: Felix		Name: Th	eeuwes						
Inventor's Felix - There Date: De 2, 1487									
RESIDENCE						,			
City: State: Count				:		Citizens			
Los Altos Hills	U.S.A.			Belgium					
POST OFFICE ADDRESS 27	350 Altamont R	oad							
City:	State		Zip:		Country:		Applicant		
Los Altos Hills	1	CA	94	94023 U.S.A.			Authority: US		
Additional inventors are being	na named on eur	onlemental	chapt(e)	attached heret	10				

Type a	a plus	sign	(+)	here	\rightarrow	+

Г	DECLAR	A	ADDITIONAL INVENTOR(S) Supplemental Sheet					
Name of Additional Joint Inven Michel J.N. Cormier	tor, if any:	A petiti	on has be	en filed for thi	s unsigned invento	or.		
Given		Middle	T	Family			Suffix:	
Name: Michel		Initial:	J.N.	Name: Co	rmier		1	
Inventor's Signature:	Corr	UER		Date:	12/3/9	7		
City:	St	ate:	Country	:		Citizenship	:	
Mountain View		CA		U.S.A.			French	
	78 Andsbury							
City:	St	ate:	Zip:		Country:		pplicant	
Mountain View Name of Additional Joint Inven	tor if one	CA	94	043	U.S.A	A. P	authority: US	
Armand P. Neukermans	tor, ir arry.	A petiti	ion has be	en filed for thi	is unsigned invent	or.		
Given Name: Armand		Middle	P.	Family Name: Ne	eukermans		Suffix:	
Inventor's	Time				.1. /	***************************************		
Signature:	unc			Date: /	1/16/97			
RESIDENCE "		oto:	Country		' '	Citizenship		
City:	31	ca Count		y: U.S.A.		Ciuzensinp	U.S.	
							100	
	510 Arbutus							
City: Palo Alto	St	tate:	Zip: 94303		Country: U.S.A.		Applicant Authority: US	
Name of Additional Joint Inver	itor, if any:	T	A petition has been filed for this unsigned inventor.					
Given Name:		Middle Initial:				Suffix:		
Inventor's		mitiai.	. Name.					
Signature:				Date:				
RESIDENCE								
City:	St	tate:	Country:			Citizenship:		
POST OFFICE ADDRESS								
City:	Si	tate:	Zip:		Country:		Applicant	
Name of Additional Joint Inver	ntor, if any:	A petit	Authority:					
Given Mic Name: Init				Family Name:			Suffix:	
Inventor's								
Signature:				Date:				
RESIDENCE City: State:			Country			Citizenship:		
Oity.	State. Country. Citizenship.						••	
POST OFFICE ADDRESS								
City:	S	State: Zip:			Country:	Applicant Authority:		
Additional Inventors are bei	ng named or	n supplemental	l sheet(s)	attached here	to.			

*

ARC 2600

DEVICE AND METHOD FOR ENHANCING TRANSDERMAL AGENT FLUX

TECHNICAL FIELD

The present invention relates to transdermal agent delivery and sampling. More particularly, this invention relates to the transdermal delivery of agents, such as peptides and proteins, through the skin of an animal, as well as the transdermal sampling of agents, such as glucose, electrolyte and substances of abuse, such as but not limited to alcohol and illicit drugs.

BACKGROUND ART

Interest in the percutaneous or transdermal delivery of peptides and proteins to the human body continues to grow with the increasing number of medically useful peptides and proteins becoming available in large quantities and pure form. The transdermal delivery of peptides and proteins still faces significant problems. In many instances, the rate of delivery or flux of polypeptides through the skin is insufficient to produce a desired therapeutic effect due to the low flux of polypeptides through skin. In addition, polypeptides and proteins are easily degradable during and after penetration of the skin, prior to reaching target cells. Likewise, the passive flux of water soluble small molecules such as salts is limited.

One method of increasing the transdermal delivery of agents relies on the application of an electric current across the body surface or on "electrotransport". "Electrotransport" refers generally to the passage of a beneficial agent, e.g., a drug or drug precursor, through a body surface such as skin, mucous membranes, nails, and the like. The transport of the agent is induced or enhanced by the application of an electrical potential, which results in the application of electric current, which delivers or enhances delivery of the agent. The electrotransport of agents through a body surface may be attained in

1

various manners. One widely used electrotransport process, iontophoresis, involves the electrically induced transport of charged ions. Electroosmosis, another type of electrotransport process, involves the movement of a solvent with the agent through a membrane under the influence of an electric field. Electroporation, still another type of electrotransport, involves the passage of an agent through pores formed by applying a high voltage electrical pulse to a membrane. In many instances, more than one of these processes may be occurring simultaneously to different extents. Accordingly, the term "electrotransport" is given herein its broadest possible interpretation, to include the electrically induced or enhanced transport of at least one charged or uncharged agent, or mixtures thereof, regardless of the specific mechanism(s) by which the agent is actually being transported. Electrotransport delivery generally increases agent delivery, particularly peptide delivery rates, relative to passive or non-electrically assisted transdermal delivery. However, further increases in transdermal delivery rates and reductions in peptide degradation during transdermal delivery are highly desirable.

One method of increasing the agent transdermal delivery rate involves pre-treating the skin with, or alternatively co-delivering with the beneficial agent, a skin permeation enhancer. The term "permeation enhancer" is broadly used herein to describe a substance which, when applied to a body surface through which the agent is delivered, enhances its flux therethrough. The mechanism may involve a reduction of the electrical resistance of the body surface to the passage of the agent therethrough, an increase in the permeability of the body surface, the creation of hydrophilic pathways through the body surface, and/or a reduction in the degradation of the agent (e.g., degradation by skin enzymes) during electrotransport.

There have been many mechanical attempts to enhance transdermal flux, such as, U. S. Patent Nos. 5,279,544 issued to Gross et al., 5,250,023 issued to •

Lee et al., and 3,964,482 issued to Gerstel et al. These devices utilize tubular or cylindrical structures generally, although Gerstel does disclose the use of other shapes, to pierce the outer layer of the skin. Each of these devices provide manufacturing challenges, limited mechanical attachment of the structure to the skin, undesirable irritation to the skin, and/or limited conductive contact with the skin.

DESCRIPTION OF THE INVENTION

The present invention is a high volume producable, low-cost device suitable for increasing transdermal flux with skin piercing protrusions and contacting a body surface over a large contact area to reduce skin irritation and enhance agent delivery or sampling. The device of the present invention pierces the stratum corneum of a body surface to form pathways through which a substance can either be introduced (i.e., delivery) or withdrawn (i.e., sampling). In one aspect, the invention comprises a plurality of protrusions for piercing the skin which extend through a connecting medium. The connecting medium assists in making substantial contact with the body surface for either delivering or sampling an agent. For an electrotransport device, the connecting medium spreads out the contact area to all the protrusions to reduce the current density at particular locations to reduce irritation.

In one aspect of the invention, the device utilizes a member having a plurality of openings therethrough, a plurality of blades integral therewith and extending downward from a first side of the member, and a connecting medium covering at least a part of the first side of the member. The device of the present invention can be used in connection with agent delivery, agent sampling or both. Delivery devices for use with the present invention include, but are not limited to, electrotransport devices, passive devices, osmotic devices and pressure driven devices. Sampling devices for use with the present invention include, but are not

limited to, reverse electrotransport devices, passive devices, and osmotic devices.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is an enlarged cross-sectional view of a skin piercing device in accordance with the present invention;

Figure 2 is an enlarged perspective view of the bottom side of a skin piercing device with a connecting medium removed therefrom for clarity in accordance with one embodiment of the present invention;

Figure 3 is a exploded perspective view of one embodiment of an electrotransport agent delivery system according to one embodiment of the present invention:

Figure 4 is a bottom plan view of the electrotransport agent delivery system of figure 3:

Figure 5 is a right side elevational view of the electrotransport agent delivery system of figure 3;

Figure 6 is a rear elevational view of the electrotransport agent delivery system of figure 3;

Figure 7 is a cross-sectional view taken along line 7-7 of the assembled electrotransport agent delivery system of figure 5;

Figure 8 is a diagrammatic cross-sectional view of a passive agent delivery system in accordance with one embodiment of the present invention; Figure 9 is a diagrammatic cross-sectional view of another embodiment of a passive agent delivery system in accordance with the present invention; and

Figure 10 is a diagrammatic cross-sectional view of an osmotic sampling system in accordance with one embodiment of the present invention.

MODES FOR CARRYING OUT THE INVENTION

Turning now to the drawings in detail, the skin piercing device 2 of the present invention is generally shown in Figure 1. Device 2 is used for the percutaneous administration or sampling of an agent. The terms "substance", "agent" and "drug" are used interchangeably herein and broadly include physiologically or pharmacologically active substances for producing a localized or systemic effect or effects in mammals including humans and primates, avians, valuable domestic household, sport or farm animals, or for administering to laboratory animals such as mice, rats, guinea pigs, and the like. These terms also include substances such as glucose, electrolyte, alcohol, illicit drugs, etc. that can be sampled through the skin. The major barrier properties of the skin, such as resistance to agent conduction, reside with the outer layer (i.e., stratum corneum). The inner division of the epidermis generally comprises three layers commonly identified as stratum granulosum, stratum malpighii, and stratum germinativum. There is essentially little or no resistance to conduction or to absorption of an agent through the stratum granulosum, stratum malpighii, and stratum germinativum. The device of the present invention is used to pierce the stratum corneum for improved delivery or sampling of an agent and to make contact with the skin over a large contact area using a connecting medium 65 (FIG. 1).

The connecting medium 65 of the present invention is predisposed on the

skin contacting side 48 of the agent delivery or sampling device. In one embodiment, the connecting medium 65 is a conduit for the agent and acts as a bridge between the agent containing or collecting reservoir 26 and the skin, thus allowing an agent to be transported unhindered therethrough. The connecting medium can be free of agent or preloaded with agent. In the embodiment of FIG. 1, the reservoir 26 is illustrated as being separate from the connecting medium 65. It should be appreciated, however, that in some embodiments there will be migration of agent into the connecting medium prior to use of the device such that the reservoir and connecting medium are not discrete, for example, the matrix in the reservoir and the connecting medium can be the same material. In addition, a separate reservoir may not be present in that the connecting medium 65 may be the reservoir for the sampled agent or the agent to be delivered. In other words, the connecting medium is capable of storing the agent to be delivered or the sampled agent.

The connecting medium 65 is either fabricated and stored dry which can be rehydrated upon use or can be packaged in the hydrated form. In a preferred embodiment, the connecting medium is an ion conducting hydrogel of a pharmaceutically acceptable grade with minimum extractable or degradation products which sorbs or contains in a functional state an amount of water in the range from 20% to 90%, preferably in the range from 30% to 70%. Preferably the connecting medium is a hydrogel that is at least slightly crosslinked to prevent fragments of polymers from penetrating the skin and has adhesive or tacky properties.

The connecting medium 65 can be any of a large variety of materials as discussed above and further including, by way of example, an organic polymer having at least some pendent substituents capable of being ionic, a polar natural material, a semi-synthetic material, a cellulosic derivative, an alginate derivative, a starch derivative, a dextran, a polysaccharide, a hydrogel polymer having a

backbone selected from the group consisting of a hydrous-gelled, linear polyolefin, polycarbonate, polyester, polyether, polyurethane and polyopoxide backbone, with backbone substituents selected from the group consisting of (alkyl, aryl or aralkyl) alcohol, amide, ketone, nitrogen heterocycle or ester pendent substituents, and any combination thereof. The connecting medium can be in a variety of forms such as a gel, solid, hydrogel, powder, liquid, viscous fluid, gauze made of cotton or other absorbent fabrics as well as pads and sponges, both natural and synthetic, may be used. Any suitable materials listed in U.S. Patent No. 5,385,543 could be used in conjunction with the present invention. U.S. Patent No. 5,423,739, issued to Phipps et al., describes iontophoretic materials and substances that can be used as the connecting medium.

Device 2 comprises a plurality of protrusions 4 extending downward from one surface of a member or plate 6 which has a connecting medium 65 (FIG. 1) on at least a portion of surface 48 (see Figure 2 in which device 2 is in an inverted position to show the protrusions and wherein the connecting medium is removed for clarity). The protrusions 4 can be blades (FIGS, 1 and 2), pins (not shown), or any of a variety of configurations for piercing the skin or body surface. The protrusions 4 penetrate the stratum corneum of the epidermis when pressure is applied to the device to increase the administration of or sampling of a substance through a body surface. The term "body surface" as used herein refers generally to the skin, mucous membranes, and nails of an animal or human, and to the outer surface of a plant. The protrusions 4 extend through the connecting medium 65 to pierce the body surface to create good agent conduction from the system into the body, or vice versa. The member 6 is formed with an opening 8 between the blades 4 for enhancing the movement of agent released from or collected in the agent containing or collecting reservoir 26. In one embodiment, the opening 8 corresponds to the portion of the member occupied

by each of the blades 4 prior to the blades being bent into a position which is substantially perpendicular to the plane of member 6. The number of openings per device and the number of blades per device are independent. In addition, the device may have only one large opening with a plurality of blades around the opening. The agent can be administered or sampled at a controlled rate of release from or collection in the reservoir 26 through an agent rate controlling material such as a flux control membrane (not shown) positioned between the reservoir 26 and the member 6.

The protrusions or blades 4 are generally formed from a single piece of material and are sufficiently sharp and long for puncturing at least the stratum corneum of the skin. In one embodiment, the blades 4 and the member 6 are essentially impermeable or are impermeable to the passage of an agent. The width of each blade can be any of a range of widths. The blades 4 can have slanted (i.e., angled) leading edges 64 (FIG. 2) to further reduce the insertion force required to press the blades into the skin tissue. The leading edges of each blade can be all be the same angle or can be at different angles suitable for piercing the skin. Alternatively, the leading edge of each blade can be arcuate (i.e., curved) in shape, having, for example, a convex or concave shape.

The device 2 of the present invention improves the attachment of the device to the skin so that a continuous agent conducting pathway through the body surface is preserved during movement of the body surface. In the embodiment shown in Figure 2, projections in the form of barbs 50 on at least one of the blades 4 assist in anchoring the device 2 and any corresponding device or structure used in combination therewith to the skin. Barbs 50 can be on any number of the blades from one blade to all blades. The barbs 50 are optional as other means for holding the device in contact with the skin can be used. The present invention can be used in conjunction with a wide variety of blade configurations, for example reference may be had to U.S. Provisional

Application No. 60/019,990 filed June 18, 1996 of which any of the disclosed configurations can be used with the present invention.

The pattern for any of the blade array devices 2 of the present invention can be produced with a photo-etching process. A thin member 6 of metal such as stainless steel or titanium is etched photo-lithographically with patterns containing blade-like structures. In general, a thin laminate dry resist or wet resist is applied on the member 6 which typically has a thickness of about 7 micrometers to about 100 micrometers, preferably about 25 micrometers to about 50 micrometers. The resist is contact exposed using a mask having the desired pattern and is subsequently developed. These operations are conducted in much the same way that they are for the manufacture of a printed circuit board. The member 6 is then etched using acidic solutions. After the pattern has been etched through the member, the member 6 is placed on a die having a plurality of openings corresponding to the openings 8 in the member. A punch having a plurality of protrusions corresponding to the openings 8 in the member 6 and openings in the die is initially located above the member and the die. At the initial stage, the blades 4 are in the same plane as the rest of the member 6. The protrusions on the punch are then pressed into the openings, thus bending the blades downward to be substantially perpendicular to the plane of the member 6. The finished structure provides blades 4 with an adjacent opening 8 for the passage of a substance therethrough when the device 2 is applied to the body surface. Rectangular openings 8 are shown in the figures but the invention encompasses the use of any shape openings including, but not limited to, square, triangular, circular and elliptical.

In one embodiment of the etching process, a dry resist (e.g., "Dynachem FL" available from Dynachem located in Tustin, CA is applied 12.5 micrometers thick to one or both sides of the member 6 and exposed in a standard manner. Then using a suitable spray etcher (e.g., "Dynamil VRP 10/NM" available from

Western Tech. Assoc. located in Anaheim, CA) a mixture of ferric chloride and hydrochloric acid is sprayed onto the resist and member 6 at 125 degrees F for two minutes. A standard caustic stripper is used for the resist removal.

In another embodiment of the etching process, a wet resist (e.g., "Shipley 111S" available from Shipley Corporation, located in Marlborough, MA) is applied 7.5 micrometers thick at about 70 degrees F to one or both sides of the member 6 and exposed in a standard manner. Then a suitable etchant (e.g., ferric chloride) is sprayed onto the resist and member at 120 degrees F. A standard caustic stripper is used for the resist removal.

Generally, the blades 4 are at an angle of about 90 degrees to the surface 48 of the member 6 after being punched, but they can be disposed at any angle forward or backward from the perpendicular position that will facilitate penetration of and attachment to the stratum corneum. In addition, other anchoring elements such as barbs, openings, etc. can be used with the angled blades to further enhance anchoring of the device.

The member 6 and blades 4 can be made from materials that have sufficient strength and manufacturability to produce blades, such as, glasses, ceramics, rigid polymers, metals and metal alloys. Examples of metals and metal alloys include but are not limited to stainless steel, iron, steel, tin, zinc, copper, silver, platinum, aluminum, germanium, nickel, zirconium, titanium and titanium alloys having nickel, molybdenum or chromium. Each of the member and blades can have a thin layer of silver, gold, platinum, iridium, titanium, rhodium plating or evaporated or sputtered biocompatible metals to provide for inertness, biocompatibility and preservation of the sharpness of the edges during storage. An example of glasses include a devitrified glass such as "Photoceram" available from Corning in Corning, NY. Examples of polymers include but are not limited to polystyrene, polymethylmethocrylate, polypropylene, "Bakelite", celluloseacetate, ethylcellulose, styrene/acrylonitrile copolymers,

stryrene/butadiene copolymers, acrylonitrile/butadiene/styrene (ABS) copolymers, polyvinyl chloride and acrylic acid polymers including polyacrylates and polymethacrylates.

The number of blades 4 and openings 8 of any of the embodiments of the device 2 is variable with respect to the desired flux rate, agent being sampled or delivered, delivery or sampling device used (i.e., electrotransport, passive, osmotic, pressure driven, etc.), and other factors as will be evident to one of ordinary skill in the art. In general, the larger the number of blades per unit area (i.e., blade density), the more uniform the flux of the agent is through the skin because there are a greater number of pathways through the skin. Consequently, the smaller the number of blades per unit area, the more concentrated the flux of the agent is through the skin because there are fewer pathways. Higher concentrations of agents in a skin pathway typically lead to higher incidences and/or severity of skin reactions (e.g., irritation). Therefore, larger blade densities reduce the incidence and/or severity of skin reactions.

One embodiment of the present invention relies on the application of an electric current across the body surface or "electrotransport". It will be appreciated by those working in the field that the present invention can be used in conjunction with a wide variety of electrotransport systems, as the invention is not limited in any way in this regard. For examples of electrotransport systems, reference may be had to U.S. Patent Nos. 5,147,296 to Theeuwes et al., 5,080,646 to Theeuwes et al., 5,169,382 to Theeuwes et al., 5,423,739 to Phipps et al., 5,385,543 to Haak et al., 5,310,404 to Gyory et al., and 5,169,383 to Gyory et al., of which any of the disclosed electrotransport systems can be used with the present invention.

Figures 3-7 illustrate a representative electrotransport delivery device 10 that may be used in conjunction with the present invention. Device 10 comprises an upper housing 16, a circuit board assembly 18, a lower housing 20, anode

electrode 22, cathode electrode 24, anode reservoir 26, cathode reservoir 28 and skin-compatible adhesive 30. Upper housing 16 has lateral wings 15 which assist in holding device 10 on a patient's skin. Printed circuit board assembly 18 comprises an integrated circuit 19 coupled to discrete components 40 and battery 32. Circuit board assembly 18 is attached to housing 16 by posts (not shown in Figure 3) passing through openings 13a and 13b, the ends of the posts being heated/melted in order to heat stake the circuit board assembly 18 to the housing 16. Lower housing 20 is attached to the upper housing 16 by means of adhesive layer 30, the upper surface 34 of adhesive layer 30 being adhered to both lower housing 20 and upper housing 16 including the bottom surfaces of wings 15. Shown (partially) on the underside of circuit board assembly 18 is a button cell battery 32. Other types of batteries may also be employed to power device 10 depending on the need.

The device 10 is generally comprised of battery 32, electronic circuitry 19,40, electrodes 22,24, agent reservoirs 26,28, and skin piercing device 2, all of which are integrated into a self-contained unit. Electrodes 22,24 and reservoirs 26,28 are retained by lower housing 20. Anodic electrode 22 is preferably comprised of a metal such as silver and cathodic electrode 24 is preferably comprised of a metal halide such as silver chloride. The outputs (not shown in Figure 3) of the circuit board assembly 18 make electrical contact with the electrodes 24 and 22 through openings 23,23' in the depressions 25,25' formed in lower housing 20, by means of electrically conductive adhesive strips 42,42'. Electrodes 22 and 24, in turn, are in direct mechanical and electrical contact with the top sides 44',44 of agent reservoirs 26 and 28. The bottom side 46 of agent reservoir 28 contacts the patient's skin through the opening 29 in adhesive layer 30. The bottom side 46' of agent reservoir 26 contacts the connecting medium through the plurality of openings 8 in the skin piercing device 2. The agent in reservoir 26 is typically a viscous gel that fills the

openings 8 such that the agent reservoir is in contact with the connecting medium 65 as can be seen in FIG. 1. As discussed above, typically the agent is present initially in both the reservoir and the connecting medium because of diffusion or because the reservoir and connecting medium are the same material. Both reservoirs 26 and 28 are preferably comprised of polymeric gel materials. A liquid agent solution or suspension is contained in at least one of the reservoirs 26 and 28.

The device 10 adheres to the patient's body surface (e.g., skin) by means of an adhesive layer 30 (which has upper adhesive side 34 and body-contacting adhesive side 36) and, optionally, anchoring elements on the device 2 of any of the embodiments discussed herein. Further, optionally, the connecting medium 65 can be tacky or adhesive for assisting in maintaining contact with the skin. The adhesive side 36 covers the entire underneath side of the device 10 except where the device 2 and cathodic electrode are located. The adhesive side 36 has adhesive properties which assures that the device 10 remains in place on the body during normal user activity, and yet permits reasonable removal after the predetermined (e.g., 24-hour) wear period. Upper adhesive side 34 adheres to lower housing 20 and retains the electrodes and agent reservoirs within housing depression 25, 25' as well as retains device 2 to lower housing 20 and lower housing 20 to upper housing 16.

In one embodiment of the agent delivery device there is a release liner (not shown) on the device 10 for maintaining the integrity of the device when it is not in use. In use, the release liner is stripped from the device before the device is applied to the skin. Device 10 also has a push button switch 12, which when pressed turns the device 10 on which is made apparent to the user by means of LED 14 becoming lit. Drug is delivered through the patient's skin (e.g., on the arm) by electrotransport over the predetermined delivery interval.

Examples of neutral or uncharged hydrogels for use in the

electrotransport system are polyvinyl alcohol crosslinked through a heating or cooling crystallization process or a combination of polyox crosslinked with carbopol or polyacrylic acid. The connecting medium can be electrically charged such as an ion exchange resin with a fixed charge and mobile counter charges. A preferred embodiment is a resin with fixed charges opposite the charge of the agent ion. An example of an ionically charged or ion exchange resin is cholestvramine.

In other embodiments of the present invention, passive transdermal delivery or sampling devices are used with a connecting medium 65 predisposed on the bottom (i.e., skin facing) surface of the device. It will be appreciated by those working in the field that the present invention can be used in conjunction with a wide variety of passive transdermal systems, as the invention is not limited in this regard. For examples of passive systems, reference may be had to, but not limited to, U.S. Patent Nos. 4,379,454 to Campbell et al., 4,588,580 to Gale et al., 4,832,953 to Campbell et al., 4,698,062 to Gale et al., 4,867,982 to Campbell et al., and 5,268,209 to Hunt at al., of which any of the disclosed systems can be used with the present invention. Two examples of passive transdermal delivery devices are illustrated in Figures 8 and 9.

In Figure 8, passive transdermal delivery device 88 comprises a reservoir 90 containing a therapeutic agent (e.g., a drug) to be delivered transdermally. Reservoir 90 is preferably in the form of a matrix containing the agent dispersed therein. Reservoir 90 is sandwiched between a backing layer 92, which is impermeable to the agent, and an optional rate-controlling membrane 94. In Figure 8, the reservoir 90 is formed of a material, such as a polymer, that is sufficiently viscous to maintain its shape. If a lower viscosity material is used for reservoir 90, such as an aqueous gel, backing layer 92 and rate-controlling membrane 94 would be sealed together about their periphery to prevent leakage. Located below membrane 94 is skin piercing device 2 with connecting medium

65 on a skin facing surface thereof which extends through the openings (not shown) in device 2 to contact membrane 94. The device 88 adheres to a body surface by means of contact adhesive layer 96 around the periphery of the device 2 and, optionally, by the anchoring elements of any of the embodiments described previously. In most instances, the connecting medium 65 will initially contain agent. A strippable release liner (not shown) is normally provided along the exposed surface of adhesive layer 96 and is removed prior to application of device 10 to the body surface.

Alternatively, as shown in enlarged Figure 9, transdermal therapeutic device 98 may be attached to a body surface by means of a flexible adhesive overlay 100. Device 98 is comprised of an agent-containing reservoir 90 which is preferably in the form of a matrix containing the agent dispersed therein. Connecting medium 65 extends through the openings 8 to contact the reservoir 90. Alternatively, the matrix in reservoir 90 can extend through the openings 8 initially to be in contact with the connecting medium 65 or the reservoir and connecting medium can be the same. An impermeable backing layer 102 is provided adjacent one surface of reservoir 90. Adhesive overlay 100 maintains the device on the body surface. Adhesive overly 100 can be fabricated together with, or provided separately from, the remaining elements of the device 98. With certain formulations, the adhesive overlay 100 may be preferable to the contact adhesive 96 shown in Figure 8. This is true, for example, where the agent reservoir contains a material (such as, for example, an oily surfactant) which adversely affects the adhesive properties of the contact adhesive layer 96. Impermeable backing layer 102 is preferably slightly larger than reservoir 90, and in this manner prevents the agents in reservoir 90 from adversely interacting with the adhesive in overlay 100. Optionally, a rate-controlling membrane (not shown in Figure 9) similar to membrane 94 in Figure 8 can be provided on the body surface side of reservoir 90. A strippable release liner (not shown) is also

normally provided with device 98 and is removed just prior to application of device 98 to the body surface.

The formulation of reservoir 90 may be aqueous or nonaqueous based. The formulation is designed to deliver the agent at the necessary fluxes. Aqueous formulations typically comprise water and about 1 to 60 weight percent of a hydrophilic polymer as a gelling agent, such as hydroxyethylcellulose, hydroxypropylcellulose, hydroxyethylmethacrylate and polymers used in soft contact lenses. Typical non-aqueous formulations are comprised of silicone fluid, silicone rubbers, hydrocarbon polymers, polyisobutylene, rubbers, or mineral oil. Mineral oil-based gels also typically contain 1 to 2 weight percent of a gelling agent such as colloidal silicon dioxide.

The reservoir matrix having agent therein should be compatible with the delivered agent, uptake inhibiting agent (if any) and any carrier therefore. When using an aqueous-based system, the reservoir matrix is preferably a hydrophilic polymer (e.g., a hydrogel). When using a non-aqueous-based system, the reservoir matrix is preferably composed of a hydrophobic polymer. Suitable polymeric matrices are well known in the transdermal drug delivery art.

When a constant agent delivery rate is desired, the agent is present in the matrix or carrier at a concentration in excess of saturation, the amount of excess being a function of the desired length of the agent delivery period of the system. The agent may, however, be present at a level below saturation without departing from this invention as long as the agent and the uptake-inhibiting agent (if any) are continuously and co-extensively administered to the same body surface site in an amount and for a period of time sufficient to reduce or eliminate skin irritation by the agent.

In addition to the agent, the connecting medium may also contain dyes, pigments, inert fillers, permeation enhancers, excipients tackifiers, neutral polymers, surfactants, reagents, buffers, plasticizers, and other conventional

components of pharmaceutical products or transdermal devices known in the art.

The amount of agent present in the reservoir and the size of the reservoir is generally non-limited and is an amount equal to or larger than the amount of agent that in its released form is effective in bringing about the desired local and/or systemic physiological and/or pharmacological effects.

The preferred form in which an agent is delivered generally determines the type of delivery system to be used, and vice versa. That is, the selection of a "passive" system which delivers the agent by diffusion or an electrically powered system which delivers the agent by electrotransport will be mostly determined by the form of the agent. For example, with passive delivery systems, it has generally been recognized that the agent is preferably delivered in either its free base or acid form, rather than in the form of a water soluble salt when the agent diffuses through the stratum corneum. On the other hand, with electrotransport delivery devices, it has been recognized that the agents should generally be soluble in water. It is generally believed that the pathways for passive and electrotransported transdermal agent delivery through intact skin are different, with passive delivery occurring through lipid regions (i.e., hydrophobic regions) of the skin and electrotransport delivery occurring through hydrophilic pathways or pores such as those associated with hair follicles and sweat glands. For the case of pierced skin, substantial passive flux through the created pathways which are aqueous can be expected. The agent for passive delivery in the case of pierced skin is generally hydrophilic (e.g., water soluble salt form) and the preferred form of an agent for electrotransport delivery is also hydrophilic (e.g., water soluble salt form). For passive delivery, a combination of ionized agent (e.g., water soluble) and unionized agent (e.g., hydrophilic) can be used.

For osmotic and pressure driven systems which deliver agents by connective flow carried by a solvent, the agent preferably has sufficient solubility in the carrier solvent. It will be appreciated by those working in the field that the present invention can be used in conjunction with a wide variety of osmotic and pressure driven systems, as the invention is not limited to a particular device in this regard. For examples of osmotic and pressure driven devices, reference may be had to U.S. Patent Nos. 4,340,480 to Eckenhoff, 4,655,766 to Theeuwes et al., 4,753,651 to Eckenhoff, 5,279,544 to Gross et al., 4,655,766 to Theeuwes, 5,242,406 to Gross et al., and 4,753,651 to Eckenhoff any of which can be used with the present invention.

This invention has utility in connection with the delivery of agents within any of the broad class of drugs normally delivered through body surfaces and membranes, including skin. In general, this includes drugs in all of the major therapeutic areas including, but not limited to, anti-infectives such as antibiotics and antiviral agents, analgesics including fentanyl, sufentanil, buprenorphine and analgesic combinations, anesthetics, anorexics, antiarthritics, antiasthmatic agents such as terbutaline, anticonvulsants, antidepressants, antidiabetic agents, antidiarrheals, antihistamines, anti-inflammatory agents, antimigraine preparations, antimotion sickness preparations such as scopolamine and ondansetron, antinauseants, antineoplastics, antiparkinsonism drugs, antipruritics, antipsychotics, antipyretics, antispasmodics, including gastrointestinal and urinary anticholinergics, sympathomimetrics, xanthine derivatives, cardiovascular preparations including calcium channel blockers such as nifedipine, beta-blockers, beta-agonists such as dobutamine and ritodrine, antiarrythmics, antihypertensives such as atenolol, ACE inhibitors such as ranitidine, diuretics, vasodilators, including general, coronary, peripheral and cerebral, central nervous system stimulants, cough and cold preparations, decongestants, diagnostics, hormones such as parathyroid hormone, bisphosphoriates, hypnotics, immunosuppressives, muscle relaxants, parasympatholytics, parasympathomimetrics, prostaglandins, psychostimulants, sedatives and tranquilizers.

The invention is also useful in the transdermal delivery of proteins, peptides and fragments thereof, whether naturally occurring, chemically synthesized or recombinantly produced. The invention may additionally be used in conjunction with the delivery of nucleotidic drugs, including oligonucleotide drugs, polynucleotide drugs, and genes. These substances typically have a molecular weight of at least about 300 daltons, and more typically have a molecular weight of at least about 300 to 40,000 daltons. Specific examples of peptides and proteins in this size range include, without limitation, LHRH, LHRH analogs such as goserelin, buserelin, gonadorelin, napharelin and leuprolide, GHRH, GHRF, insulin, insultropin, calcitonin, octreotide, endorphin, TRH, NT-36 (chemical name: N-[[(s)-4-oxo-2-azetidinyl]carbonyl]-L-histidyl-L-prolinamide), liprecin, pituitary hormones (e.g., HGH, HMG, desmopressin acetate, etc), follicle luteoids, aANF, growth factors such as growth factor releasing factor (GFRF), \(\beta MSH, GH, \) somatostatin, bradykinin. somatotropin, platelet-derived growth factor, asparaginase, bleomycin sulfate, chymopapain, cholecystokinin, chorionic gonadotropin, corticotropin (ACTH), erythropoietin, epoprostenol (platelet aggregation inhibitor), glucagon, HCG, hirulog, hyaluronidase, interferon, interleukins, menotropins (urofollitropin (FSH) and LH), oxytocin, streptokinase, tissue plasminogen activator, urokinase, vasopressin, desmopressin, ACTH analogs, ANP, ANP clearance inhibitors. angiotensin II antagonists, antidiuretic hormone agonists, bradykinin antagonists, ceredase, CSI's, calcitonin gene related peptide (CGRP), enkephalins, FAB fragments, IgE peptide suppressors, IGF-1, neurotrophic factors, colony stimulating factors, parathyroid hormone and agonists, parathyroid hormone antagonists, prostaglandin antagonists, pentigetide, protein C, protein S, renin inhibitors, thymosin alpha-1, thrombolytics, TNF, vaccines, vasopressin antagonists analogs, alpha-1 antitrypsin (recombinant), and TGF-beta.

As mentioned, the device 2 of the present invention can also be used with

sampling devices including, but not limited to, reverse electrotransport (i.e., iontophoresis and/or electroosmosis), osmosis, and passive diffusion. Figure 10 illustrates an osmotic sampling device 104 in combination with any of the embodiments described previously for device 2 with connecting medium 65. Osmotic sampling devices can be used to sample any of a variety of agents through a body surface including, but not limited to glucose, electrolyte, alcohol and illicit substances (e.g., drugs of abuse). The osmotic sampling device 104 is attached to a body surface by means of a flexible adhesive overlay 100. Device 104 is comprised of a salt layer 106 separated by semi-permeable membrane 95 from a layer 94 which stores the agent to be sampled. The layer 94 is absorbant in character in that the layer (e.g., hydrogel) passes fluid drawn through the body surface but retains the agent being sampled. The device 2 with connecting medium 65 thereon is in contact with layer 94 such that the projections on device 2 pierce the body surface and the connecting medium 65 makes good contact with the body surface. The salt layer 106 draws fluid from the body by osmosis through the connecting medium 65 and layer 94. The fluid drawn from the body contains the agent being sampled. As the fluid containing the agent passes through layer 94, the agent is retained in layer 94 and the fluid is absorbed by the salt layer 106. Preferably, the salt layer is free to expand or is encapsulated in a semi-permeable membrane 95 so that it retains the fluid therein. The sampled agent can be measured in situ directly or withdrawn from the layer 94 and sampled by conventional means.

Alternatively, salt layer 106, layer 94 and semi-permeable membrane 95 can be combined in one layer of absorbant hydrogel that stores the absorbed fluid as well as the agent sampled. Additionally, this one layer can be configured as the connecting medium 65 thereby greatly simplifying the device.

The following example is merely illustrative of the present invention and should not be considered as limiting the scope of the invention in any way, as

this example and other equivalents thereof will become apparent to those versed in the art and in light of the present disclosure, drawings, and the accompanying claims.

Example 1

The effect of the present invention is evaluated for its effect on drug flux and the skin resistance of a hairless guinea pig during electrotransport delivery of a model decapeptide drug. The following are specifications for the device. The device consists of a member having a plurality of rectangular openings having two blades, one on each end of a 0.25 mm² void area for each opening. The openings are aligned in pairs with every other pair of openings oriented 90 degrees to the previous pair of openings. All of the blades are about 500 micrometers long. There are 256 void areas per cm² and 512 blades per cm². An electrotransport system is used which applies a constant current of 0.1 mA/cm². It consists of a cathode counter reservoir comprising a Dulbelco's phosphate buffered saline imbibing gel and a donor anode reservoir comprising a hydroxyethylcellulose gel containing an aqueous solution of decapeptide bufferred at pH 7.5. The electrotransport system is placed on the skin of a lightly anesthetized hairless guinea pig. Decapeptide flux is evaluated by measuring urinary excretion of this peptide. Use of the present invention results in increased decapeptide flux over the transport period compared to an ordinary electrotransport device.

It will be appreciated by those of ordinary skill in the art that the invention can be embodied in other specific forms without departing from the spirit or essential character thereof. The presently disclosed embodiments are therefore considered in all respects to be illustrative and not restrictive. The scope of the invention is indicated by the appended claims rather than the foregoing description, and all changes which come within the meaning and range

of equivalents thereof are intended to be embraced therein.

CLAIMS:

 A device for introducing or withdrawing an agent through a body surface, comprising:

a member having a plurality of protrusions extending from a body surface contacting side of the member; and

a connecting medium capable of storing the agent therein or passing the agent therethrough on at least a portion of the body surface contacting side of the member.

- 2. The device of Claim 1 wherein the member has an opening therethrough.
- The device of Claim 2 wherein the connecting medium extends across the opening.
- The device of Claim 2 wherein the connecting medium extends through the opening.
- 5. The device of Claim 2 wherein the connecting medium is in the opening.
- The device of Claim 1 wherein the connecting medium is in the range of about 10 micrometers to about 100 micrometers thick.
- The device of Claim 1 wherein the connecting medium is about 50 micrometers thick.
- The device of Claim 1 wherein the connecting medium comprises a hydrogel.

- The device of Claim 1 wherein the connecting medium is preloaded with the agent to be delivered through the body surface.
- 10. The device of Claim 1 wherein the connecting medium comprises a form selected from the group consisting of a gel, a solid and a powder.
- 11. The device of Claim 1 wherein the connecting medium further comprises a matrix material.
- 12. The device of Claim 1 wherein the protrusions comprise blades.
- 13. The device of Claim 12 wherein at least one of the plurality of blades comprises means for anchoring the device to the body surface.
- 14. The device of Claim 1 further comprising an agent delivery device connected to a second side of the member, the agent delivery device selected from the group consisting of an electrotransport device, a passive device, an osmotic device, and a pressure driven device.
- 15. The device of Claim 14 wherein the agent is selected from the group consisting of a gene, a polypeptide, and a protein.
- 16. The device of Claim 1 further comprising a sampling device connected to a second side of the member, the sampling device selected from the group consisting of a reverse electrotransport device, a passive device, and an osmotic device.
- 17. The device of Claim 16 wherein a sampled agent is selected from the

group consisting of body electrolytes, illicit drugs and glucose.

18. A device for introducing or withdrawing an agent through a body surface, the device comprising:

a plurality of protrusions extending from a first side and an opening through the device between the protrusions; and

a connecting medium capable of storing the agent therein or passing the agent therethrough being predisposed in the opening.

- 19. The device of Claim 18 wherein the connecting medium is predisposed on a portion of the first side.
- 20. The device of Claim 18 wherein the agent is selected from the group consisting of a gene, a polypeptide, and a protein.
- 21. The device of Claim 18 wherein the connecting medium comprises a hydrogel.
- 22. The device of Claim 18 wherein the connecting medium is preloaded with an agent to be delivered through the body surface.
- 23. A method for introducing or withdrawing an agent through a body surface, comprising the steps of:

piercing the body surface with a plurality of protrusions extending from a first side of a member having a connecting medium capable of storing the agent therein or passing the agent therethrough on at least a portion of the first side;

contacting the body surface with the connecting medium; and passing the agent through the body surface.

- 24. The method of Claim 23 wherein the passing step comprises: administering the agent by a method selected from the group consisting of electrotransport, passive delivery, osmosis, and pressure.
- 25. The method of Claim 23 wherein the passing step comprises: sampling the agent by a method selected from the group consisting of reverse electrotransport, passive sampling, and osmosis.

ABSTRACT OF THE DISCLOSURE

An agent delivery or sampling device (2) comprising a member (6) having a plurality of blades (4) for piercing the skin and a connecting medium (65) covering at least a part of the skin contacting side (48) of the member (6) for increasing transdermal flux of an agent.















